

Superlight SL2557 WDL Up or Down LED Wall Light

Superlight SL2557 up or down LED wall mounted light fittings are suitable for large scale commercial and industrial projects that require high-performance illumination. The fixtures incorporate integral constant current LED driver and are protected to IP65 making them suitable for any interior or exterior environment.

SPECIFICATIONS

Input Voltage:	100-265VAC
LED Driver Configuration:	Integral, Constant Current
Power Consumption:	1x26W or 1x39W
Body Diameter	180mm
Overall Height:	280mm
Overall Width:	240mm
Fixture Material:	Extruded Alloy/Powdercoated
Standard Colour Finishes	Black or Matt Grey
LED Classification:	XP-E LED
Typical Light Source Efficacy:	95lm/W
Light Source CRI:	→85
Beam Angle:	1x24°
Recommended Ambient Temperature:	-20 ~ +45°C
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

- SL2557 CCT: 6500K CRI: →85 
- SL2557 CCT: 4200K CRI: →85 
- SL2557 CCT: 3200K CRI: →85 

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial exterior lighting, facade lighting, pillar and column highlighting, hospitality projects, industrial projects, retail environments, warehouse and industrial projects.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Optional 24VDC version available by special request

Fixture colour can be refinished by special request

Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL2557**39W-3200K WDL557 Up or Down LED Wall Light 100-265VAC 2x39W
- SL2557**39W-4200K WDL557 Up or Down LED Wall Light 100-265VAC 2x39W
- SL2557**39W-6500K WDL557 Up or Down LED Wall Light 100-265VAC 2x39W
- SL2557**26W-3200K WDL557 Up or Down LED Wall Light 100-265VAC 2x26W
- SL2557**26W-4200K WDL557 Up or Down LED Wall Light 100-265VAC 2x26W
- SL2557**26W-6500K WDL557 Up or Down LED Wall Light 100-265VAC 2x26W

**Specify fixture colour Black = BK / Matt Grey = GY

