

SL3493 Grid-150 Series Recessed LED Downlight

Superlight Grid-150 series is a commercial grade recessed LED downlight suitable for premium interior fitouts. The fitting is constructed from quality materials and incorporates high efficiency dimmable LED technology. Grid-150 series is available in matching one, two and three gang options.

SPECIFICATIONS

Driver Input Voltage:	100-240VAC
Power Consumption:	45W
Trim Dimensions:	458x176mm
Fixture Depth:	110mm
Ceiling Cutout:	440x162mm
LED Classification:	Sharp COB 350mA
LED Quantity:	3
Fixture Material:	Extruded Body & Aluminium Reflector
Typical Light Source Efficacy:	90lm/W
Light Source CRI	90
Beam Angle Options:	45°/60°
Adjustable Tilt Angle:	360° Swivel + 35° Tilt
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP44

PHOTOMETRIC INFORMATION

- SL3493-15 CCT: 5000K CRI: →90 ●
- SL3493-17 CCT: 4000K CRI: →90 ●
- SL3493-21 CCT: 3000K CRI: →90 ●
- SL3493-27 CCT: 2700K CRI: →90 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial interior projects, retail spaces, shopping malls, showrooms, hospitality projects, hotels, common areas, galleries and display areas, shoplighting, high ceiling lighting, airports, museums.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Superlight Grid-150 LED downlights are supplied with phase control dimmable LED drivers. Optional DALI dimmable LED driver is available by special request.

CUSTOMIZATION OPTIONS

Fixture trim can be refinished in Black/Silver/Satin Chrome
Optional DALI dimmable LED driver available by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL3493D45-27Grid-150 LED Downlight WHITE 458x176mm 45° 2700K ●
- SL3493D45-21Grid-150 LED Downlight WHITE 458x176mm 45° 3000K ●
- SL3493D45-17Grid-150 LED Downlight WHITE 458x176mm 45° 4000K ●
- SL3493D45-15Grid-150 LED Downlight WHITE 458x176mm 45° 5000K ●
- SL3493D60-27Grid-150 LED Downlight WHITE 458x176mm 60° 2700K ●

