

## Superlight Satellite SL2969 LED Track Spotlight

Superlight Satellite is a high quality LED light fixture suitable for track mounting. The product can be configured with a variety of versions, including different main colour, inner ring colours and also a variety of LED light source colour temperatures. The Satellite series is available with either single-circuit or three-circuit track adaptors.

### SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	23W
Body Length:	150mm
Body Diameter:	80mm
LED Classification:	CREE XA LED
LED Quantity:	1
Standard Colour Options:	White/Black
Inner Baffle Ring Options:	White/Black
Fixture Material:	Aluminium Alloy
Typical Light Source Efficacy:	110lm/W
Beam Angle Options:	24° / 60°
Track Adaptor Options:	Single Circuit/Three Circuit
Adjustable Angle:	360° Swivel / 100° Tilt
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

- SL2969\* -15 CCT: 5000K CRI: →90 ●
- SL2969\* -17 CCT: 4000K CRI: →90 ●
- SL2969\* -21 CCT: 3000K CRI: →90 ●
- SL2969\* -27 CCT: 2700K CRI: →90 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Residential and commercial interiors, task lighting, spotlighting, retail and show-room environments, galleries, museums, shopfitting projects, architectural high-lighting.

### CONTROL & DIMMING COMPATIBILITY

SL2969 track light series is available with either single circuit or three circuit track adaptor. Superlight can supply complete track lighting systems including hardware and accessories.

### CUSTOMIZATION OPTIONS

Fixture colour available in WHITE or BLACK  
Other fixture colours available by special request  
Inner ring colour options include WHITE or BLACK

\*\*Custom options may be subject to minimum order quantities

### ORDERING INFORMATION

- Series Model Number: SL2969 Dimmable

\*\*Specify beam angle: 20° / 38°

\*\*Specify fixture colour: WHITE/BLACK

\*\*Specify inner ring colour: WHITE/BLACK

\*\*Specify track adaptor: SINGLE CIRCUIT/THREE CIRCUIT

