

## Superlight Lido-120 Inground Linear LED Fixture

Superlight Lido-120 series is a high quality linear LED fixture suitable for inground installations. The fixtures are ideal for facade lighting and architectural feature lighting for commercial projects. The fixtures incorporate high-grade tempered glass lens and stainless steel trim.

### SPECIFICATIONS

Model:	Lido-120 Series (120° Optic)
Input Voltage:	100-240VAC
Power Consumption:	6W-32W
Nominal Lengths Available:	350mm/650mm/920mm
Overall Width:	110mm
Overall Depth:	120mm
Fixture Materials:	Stainless Steel and Glass
Included Accessories:	Mounting Housing
LED Classification:	XP-E / 3528SMD LED
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	→85
Beam Angle:	120°
Recommended Ambient Temperature:	-35 ~ +55°C
IP Protection Rating:	IP67

### PHOTOMETRIC INFORMATION

- SL4062 Lido-120 CCT: 5700K CRI: →85 ●
- SL4062 Lido-120 CCT: 4000K CRI: →85 ●
- SL4062 Lido-120 CCT: 3000K CRI: →85 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Exterior inground lighting, uplighting, signage & billboards, public spaces, streetscaping, landscape lighting, parks and recreation, retail environments, hotels & hospitality projects, industrial lighting, trafficable areas.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CUSTOMIZATION OPTIONS

Superlight Lido series is also available with narrow beam optics

Stainless steel trim can be refinished by special request

24VDC version available by special request

Minimum order quantities apply for custom options

### ORDERING INFORMATION

- SL4062K120 Lido Inground XPE Linear Fixture 350mm 120deg 10.8W
- SL4063K120 Lido Inground XPE Linear Fixture 650mm 120deg 21.6W
- SL4064K120 Lido Inground XPE Linear Fixture 920mm 120deg 32.4W
- SL4062SMD120 Lido Inground SMD Linear Fixture 350mm 120deg 6W
- SL4063SMD120 Lido Inground SMD Linear Fixture 650mm 120deg 13W
- SL4064SMD120 Lido Inground SMD Linear Fixture 920mm 120deg 18W

\*\* Specify CCT colour temperature 3000K/4000K/5700K

