

SL2878 STATIC INTERIOR LED STEPLIGHT

Superlight SL2878 fittings are stylish recessed fittings suitable for interior applications. The fitting has a indirect reflector and frosted glass lens which makes them ideal for installation at low levels. The XR 3W LED module produces smooth light output whilst producing very little heat.

SPECIFICATIONS

Input Voltage:	240V
Power Consumption:	3 Watts
LED Quantity:	1
LED Classification:	CREE High Power XR 3W
Integral LED Driver:	Yes
Trim Dimensions:	80mm x 80mm
Standard Trim Colour/Finish:	Anodised Silver
Lens:	Frosted Glass
Colour Temperature (cw/ww):	6500K/3200K
Low Energy:	Yes
IP Protection Rating:	IP20
Optional Accessory:	Mounting Wall Box

PHOTOMETRIC INFORMATION

- SL2878-15 CCT: 6500K CRI: →80 ●
- SL2878-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Applications include architectural step-lighting in residential projects, clubs & pubs, office fit-outs, hospitality areas etc.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Trim colour can be refinished

Dali dimmable driver options available by special request

Can be supplied in 12VDC RGB version

Optional render wall mount kit available seperately

Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

- SL2878-15 Silver 3W Recessed LED Steplight 6500K COOL WHITE ●
- SL2878-21 Silver 3W Recessed LED Steplight 3200K WARM WHITE ●
- SL2678-15 White 3W Recessed LED Steplight 6500K COOL WHITE ●
- SL2678-21 White 3W Recessed LED Steplight 3200K WARM WHITE ●

