

SL3032 38W COMMERCIAL LED DOWNLIGHTER

Superlight SL3032 is a general purpose commercial LED downlighter suitable for a wide range of demanding commercial applications. The fittings are ideal for large scale commercial projects where a high quality and efficient light source is required.

SPECIFICATIONS

Input Voltage:	240VAC
Max Power Consumption:	32W
LED Quantity:	72
LED Classification:	Samsung SMD LED
Standard Viewing Angle:	120°
Power Factor:	>0.9
IP Rating:	IP44
Fixture Dimensions:	220x200mm
Ceiling Cutout:	195x195mm
Min Ceiling Depth Required:	70mm
Recommended Operating Temp:	-5°C ~ +55°C

PHOTOMETRIC INFORMATION

- SL3032-15 CCT: 6500K CRI: →80 ●
- SL3032-17 CCT: 4200K CRI: →85 ●
- SL3032-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial lighting installations, Shoplighting and retail fit-outs, Commercial kitchens & foodhandling areas.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Trim colour can be refinished

Dali dimmable driver available by request

Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

- SL3032-15 32W Commercial LED Downlighter 6500K COOL WHITE ●
- SL3032-17 32W Commercial LED Downlighter 4200K NEUTRAL WHITE ●
- SL3032-21 32W Commercial LED Downlighter 3200K WARM WHITE ●

Product specifications & details are subject to change without notice.

