

SL3033 Round LED Shoplight Fitting

Commercial recessed LED shoplighter fitting with high power 38W LED. They incorporate a 45° adjustable gimbal feature which allows them to be positioned optimally for illumination of displays, retail spaces, galleries as well as general area lighting applications. They are an ideal replacement for conventional metal halide style downlights.

SPECIFICATIONS

Driver Input Voltage:	240 VAC
Max Power Consumption:	38W
LED Quantity:	Single Multi-Chip LED
LED Classification:	Samsung SMD
Viewing Angle:	60°
Fixture Adjustable:	45° Gimbal
IP Rating:	IP20
Ceiling Cutout:	165 - 185mm
Trim Dimensions:	195mm
Max Fitting Height:	132mm
Recommended Operating Temp:	-5°C ~ +55°C

PHOTOMETRIC INFORMATION

- SL3033-15 CCT: 6500K CRI: →80 ●
- SL3033-17 CCT: 4200K CRI: →82 ●
- SL3033-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial and retail projects, Museum, galleries and showrooms, Replacement for conventional metal halide downlights

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

- Colour can be refinished by request
- Dali dimmable driver available by request
- Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

- SL3033-15 38W Adj. LED Shoplighter Fitting 6500K COOL WHITE ●
- SL3033-17 38W Adj. LED Shoplighter Fitting 4200K NEUTRAL WHITE ●
- SL3033-21 38W Adj. LED Shoplighter Fitting 3000K WARM WHITE ●

Product specifications & details are subject to change without notice.

