

SL3310 SQUARE LED DOWNLIGHTER 10W

Superlight SL3310 is a square commercial recessed 10W LED downlighter which can be used for residential or commercial projects. The fittings incorporate a single powerful MX series LED and are supplied complete with dimmable LED driver.

SPECIFICATIONS

Driver Input Voltage:	85 - 265 VAC
Max Power Consumption:	10W
LED Quantity:	1
LED Classification:	MX High Power COB
Viewing Angle:	90°
Trim Dimensions:	155 x 155mm
Ceiling Cutout:	140 x 140mm
Maximum Ceiling Depth Required:	59mm
Dimmable:	Yes
IP Rating:	IP44
Recommended Operating Temp:	-5°C ~ +55°C

PHOTOMETRIC INFORMATION

- SL3310-15 CCT: 6500K CRI: →80 ●
- SL3310-21 CCT: 3200K CRI: →85 ●

Fitting colour can be refinished by request

TYPICAL APPLICATIONS

Commercial and residential projects, Food handling areas, Common area down-lighting

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

- Residential Application Ceiling Height: 2.4-3.0m
- Commercial Application Ceiling Height: 2.4-3.0m

CONTROL & DIMMING COMPATIBILITY

SL3310 LED downlighters are supplied complete with dimmable LED drivers. They are compatible with most universal style dimmers.

CUSTOMIZATION OPTIONS

Trim colour can be refinished

Dali dimmable driver available by request

Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

- SL3310-15 10W LED Downlighter Fitting 6500K COOL WHITE ●
- SL3310-21 10W LED Downlighter Fitting 3200K WARM WHITE ●

Product specifications & details are subject to change without notice.

