

## SL3330 SQUARE LED DOWNLIGHTER 30W

Superlight SL3330 is a square commercial recessed 30W LED downlighter which can be used for residential or commercial projects. The fittings incorporate a single powerful MX series LED and are supplied complete with dimmable LED driver.

### SPECIFICATIONS

Driver Input Voltage:	85 - 265 VAC
Max Power Consumption:	30W
LED Quantity:	1
LED Classification:	MX High Power COB
Viewing Angle:	90°
Trim Dimensions:	222 x 222mm
Ceiling Cutout:	205 x 205mm
Maximum Ceiling Depth Required:	59mm
Dimmable:	Yes
IP Rating:	IP44
Recommended Operating Temp:	-5°C ~ +55°C

### PHOTOMETRIC INFORMATION

- SL3330-15 CCT: 6500K CRI: →80 ●
- SL3330-21 CCT: 3200K CRI: →85 ●

Fitting colour can be refinished by request

### TYPICAL APPLICATIONS

Applications include task lighting in offices, boardrooms, kitchen island lighting, museums, galleries, retail environments, cafes etc.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

- Residential Application Ceiling Height: 3.0-4.8m
- Commercial Application Ceiling Height: 3.0-4.8m

### CONTROL & DIMMING COMPATIBILITY

SL3330 LED downlighters are supplied complete with dimmable LED drivers. They are compatible with most universal style dimmers.

### CUSTOMIZATION OPTIONS

Trim colour can be refinished by request

Dali dimmable driver available by request

Customisation options are subject to availability and minimum order quantities

### ORDERING INFORMATION

- SL3320-15 20W LED Downlighter Fitting 6500K COOL WHITE ●
- SL3320-21 20W LED Downlighter Fitting 3200K WARM WHITE ●

Product specifications & details are subject to change without notice.

