

## SL3430 40W RECESSED LED SHOPLIGHTER

Commercial recessed LED shoplighter fitting with high power 40W LED. They incorporate a 45° adjustable feature which allows them to be positioned optimally for illumination of displays, retail spaces, galleries as well as general area lighting applications. They are an ideal replacement for conventional rectangle metal halide shoplighter downlights.

### SPECIFICATIONS

Driver Input Voltage:	240VAC
Max Power Consumption(Watts):	40W
LED Classification:	Sharp Single C-T LED
LED Quantity:	1
Viewing Angle:	80°
Fixture Adjustable:	45° Tilt Gimble
IP Rating:	IP20
Ceiling Cutout:	220 x 125mm
Trim Dimensions:	235 x 145mm
Max Fitting Height:	145mm
Recommended Operating Temp:	-5 ~ +55°C

### PHOTOMETRIC INFORMATION

- SL3430-15 CCT: 6500K CRI: →80 ●
- SL3430-17 CCT: 4200K CRI: →85 ●
- SL3430-21 CCT: 3000K CRI: →85 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Commercial and retail projects, Museum, galleries and showrooms, Replacement for conventional metal halide downlights

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CUSTOMIZATION OPTIONS

Trim colour can be refinished

Dali dimmable driver available by request

Customisation options are subject to availability and minimum order quantities

### ORDERING INFORMATION

- SL3430-15 40W Adj. LED Shoplighter Fitting 6500K COOL WHITE ●
- SL3430-17 40W Adj. LED Shoplighter Fitting 4200K NEUTRAL WHITE ●
- SL3430-21 40W Adj. LED Shoplighter Fitting 3000K WARM WHITE ●

