

SL3692 EXTERIOR LED WALL LIGHT

The 3690 series wall lights are IP65 rated for all outdoor areas. They are very low energy fittings consuming less than 3 watts each. They incorporate ribbed reflector panels for smooth indirect lighting of pathways, steps, landscape applications, walkways, public areas etc. The fittings operate with 240V so no additional power supply or transformer is required. Suitable for all commercial & residential projects.

SPECIFICATIONS

Input Voltage:	240V
Max Power Consumption:	3W
LED Quantity:	20
LED Classification:	Super Bright 3648 LED
Standard Viewing Angle:	60°
Trim Dimensions:	105mm x 171mm
Fitting Depth:	65mm
Mounting Box Included:	Yes
Mounting Depth Required:	65mm (plus optional mounting can)
Operating Temperature:	-10°C ~ +65°C
Weight:	0.74Kg
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

• SL3692-11	Typical Wavelength: RED 650nm	●
• SL3692-12	Typical Wavelength: GREEN 560nm	●
• SL3692-13	Typical Wavelength: BLUE 450nm	●
• SL3692-15	CCT: 6500K CRI: →70	●
• SL3692-21	CCT: 3200K CRI: →75	●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial & residential landscape lighting, Exterior steplighting.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Fitting colour can be refinished by request
12/24VDC RGB version also available
Low voltage conversion available by request
Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

• SL3692-11	IP65 Recessed LED Wall Light RED	●
• SL3692-12	IP65 Recessed LED Wall Light GREEN	●
• SL3692-13	IP65 Recessed LED Wall Light BLUE	●
• SL3692-14	IP65 Recessed LED Wall Light AMBER	●
• SL3692-15	IP65 Recessed LED Wall Light COOL WHITE	●
• SL3692-21	IP65 Recessed LED Wall Light WARM WHITE	●

