

SL3861 Surface Mounted LED Brick Light

Superlight SL3861 is a surface mounted light fitting that features a transparent polycarbonate lens which is suitable for displaying indication decals such as a unit number or house number. The SL3861 features integral LED driver and discrete high performance LED light source. The fitting is an ideal solution for low level wall lighting where a surface mounted solution is desired.

SPECIFICATIONS

| | |
|----------------------------------|---------------------------|
| Input Voltage: | 100-240VAC |
| Max Power Consumption: | 10W |
| Dimensions: | 242x122x60mm |
| LED Classification: | Superlight SMD |
| LED Quantity: | 1 |
| Colour/Finish: | Opal Grey or Charcoal |
| Fixture Material: | Aluminium & Polycarbonate |
| Typical Light Source Efficacy: | 80lm/W |
| Included Accessories: | Wall Mount Bracket Plate |
| Recommended Ambient Temperature: | -10 ~ +40°C |
| IP Protection Rating: | IP64 |

PHOTOMETRIC INFORMATION

- SL3861 CCT: 6500K CRI: →80 ●
- SL3861 CCT: 4000K CRI: →80 ●
- SL3861 CCT: 3000K CRI: →80 ●

TYPICAL APPLICATIONS

Landscape and garden lighting. Signage and indicator purposes.
Display unit number or house number.

3D Modelling & Lighting Design

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Superlight can supply customised adhesive decal by special request
Fixture colour can be refinished by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL3861GY-21 LED Wall Light OPAL GREY Clear Lens IP64 3000K ●
- SL3861GY-17 LED Wall Light OPAL GREY Clear Lens IP64 4000K ●
- SL3861GY-15 LED Wall Light OPAL GREY Clear Lens IP64 6500K ●
- SL3861CH-21 LED Wall Light CHARCOAL Clear Lens IP64 3000K ●
- SL3861CH-17 LED Wall Light CHARCOAL Clear Lens IP64 4000K ●
- SL3861CH-15 LED Wall Light CHARCOAL Clear Lens IP64 6500K ●

