

SL3862 Surface Mounted LED Brick Light

Superlight SL3862 is a surface mounted light fitting that features a transparent polycarbonate lens which is suitable for displaying indication decals such as a unit number or house number. The SL3862 features integral LED driver and discrete high performance LED light source. The fitting is an ideal solution for low level wall lighting where a surface mounted solution is desired.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	10W
Dimensions:	242x122x60mm
LED Classification:	Superlight SMD
LED Quantity:	1
Colour/Finish:	Opal Grey or Charcoal
Fixture Material:	Aluminium & Polycarbonate
Typical Light Source Efficacy:	80lm/W
Included Accessories:	Wall Mount Bracket Plate
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP64

PHOTOMETRIC INFORMATION

- SL3862 CCT: 6500K CRI: →80 ●
- SL3862 CCT: 4000K CRI: →80 ●
- SL3862 CCT: 3000K CRI: →80 ●

TYPICAL APPLICATIONS

Landscape and garden lighting. Signage and indicator purposes.
Display unit number or house number.

3D Modelling & Lighting Design

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Standard colour options: Opal Grey or Charcoal
Fixture colour can be refinished by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL3862GY-21 Surface Mount LED Wall/Step Light OPAL GREY IP64 3000K ●
- SL3862GY-17 Surface Mount LED Wall/Step Light OPAL GREY IP64 4000K ●
- SL3862GY-15 Surface Mount LED Wall/Step Light OPAL GREY IP64 6500K ●
- SL3862CH-21 Surface Mount LED Wall/Step Light CHARCOAL IP64 3000K ●
- SL3862CH-17 Surface Mount LED Wall/Step Light CHARCOAL IP64 4000K ●
- SL3862CH-15 Surface Mount LED Wall/Step Light CHARCOAL IP64 6500K ●

