

SL4067 Stainless Steel LED Downlight

Superlight SL4067 is a high quality marine grade LED downlight suitable for all types of projects including harsh & hazardous environments. The downlight body is constructed from stabilised polycarbonate and features genuine 316 stainless steel trim with tempered glass lens.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	11W
Trim Diameter:	130mm Diameter
Ceiling Cutout:	125mm
LED Classification:	Superlight COB
LED Quantity:	1
Colour/Finish:	Brushed Stainless Steel
Fixture Material:	316 Stainless Steel Marine Grade
Typical Light Source Efficacy:	85lm/W
Beam Angle Options:	25° / 60°
Recommended Ambient Temperature:	-20 ~ +50°C
IP Protection Rating:	IP67

PHOTOMETRIC INFORMATION

- SL4067-15 CCT: 5000K CRI: →80 ●
- SL4067-17 CCT: 4000K CRI: →80 ●
- SL4067-21 CCT: 3000K CRI: →80 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Applications include exterior lighting, wet areas, marine locations, harsh environments, hazardous locations, retail and hospitality projects, industrial projects.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Stainless steel trim can be refinished by special request

Optional remote DALI dimmable driver by request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL4067-15 316 Stainless Steel LED Downlight 11W LED 60deg 5000K ●
- SL4067-17 316 Stainless Steel LED Downlight 11W LED 60deg 4000K ●
- SL4067-21 316 Stainless Steel LED Downlight 11W LED 60deg 3000K ●
- SL4067D25-15 316 Stainless Steel LED Downlight 11W LED 25deg 5000K ●
- SL4067D25-17 316 Stainless Steel LED Downlight 11W LED 25deg 4000K ●
- SL4067D25-21 316 Stainless Steel LED Downlight 11W LED 25deg 3000K ●

