

## SL4267 Exterior Commercial LED Downlight

Superlight SL4267 is a commercial grade LED downlight suitable for large scale projects requiring a robust and powerful downlight solution. The fitting features toughened construction and high powered LED light source with integral LED driver.

### SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	44W
Trim Diameter:	220mm Trim Diameter
Ceiling Cutout:	210mm Cutout
Ceiling Depth Required:	250mm Depth
LED Classification:	Superlight COB
LED Quantity:	1
Colour/Finish:	Black Powdercoat
Fixture Material:	Steel & Alloy
Typical Light Source Efficacy:	80lm/W
Beam Angle Options:	30° / 60°
Recommended Ambient Temperature:	-20 ~ +50°C
IP Protection Rating:	IP67

### PHOTOMETRIC INFORMATION

- SL4267-15 CCT: 5600K CRI: →80 ●
- SL4267-17 CCT: 4200K CRI: →80 ●
- SL4267-21 CCT: 3000K CRI: →80 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Applications include exterior lighting, airports, malls, galleries and auditoriums, marine locations, harsh environments, hazardous locations, convention centres, retail and hospitality projects, industrial projects.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CUSTOMIZATION OPTIONS

Optional DALI dimmable driver by request

Fixture colour can be refinished by special request

\*\*Custom options may be subject to minimum order quantities

### ORDERING INFORMATION

- SL4267-15 Exterior LED Downlight 220mm IP67 44W LED 60° 5600K ●
- SL4267-17 Exterior LED Downlight 220mm IP67 44W LED 60° 4200K ●
- SL4267-21 Exterior LED Downlight 220mm IP67 44W LED 60° 3000K ●
- SL4267D30-15 Exterior LED Downlight 220mm IP67 44W LED 30° 5600K ●
- SL4267D30-17 Exterior LED Downlight 220mm IP67 44W LED 30° 4200K ●
- SL4267D30-21 Exterior LED Downlight 220mm IP67 44W LED 30° 3000K ●

