




Superlight SL6067 LED Bollard Fixture

Superlight SL6067 LED is a high quality LED bollard fixture for garden and landscape lighting applications. The fitting is constructed from high-grade materials and is suited for any commercial or residential project.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	10W
Overall Height:	800mm
Bollard Profile Dimensions:	92x92mm
Head Dimension:	150mm
LED Classification:	Superlight High Power LED
LED Quantity:	1
Colour/Finishes:	Opal Grey / Charcoal
Fixture Material:	Extruded Alloy
Typical Light Source Efficacy:	75lm/W
Included Accessories:	Mounting Bracket Included
Recommended Ambient Temperature:	-10 ~ +50°C
IP Protection Rating:	IP64

PHOTOMETRIC INFORMATION

- SL6067-15  CCT: 6500K CRI →80
- SL6067-17  CCT: 4000K CRI →80
- SL6067-21  CCT: 3000K CRI →80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Apartment complexes, garden & landscape lighting, public spaces, pathways, parks, driveways.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Fixture height can be customised by special request

Colour can be refinished by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL6067GY-21 Bollard 800mm OPAL GREY IP64 100-240VAC 10W 3000K 
- SL6067GY-17 Bollard 800mm OPAL GREY IP64 100-240VAC 10W 4000K 
- SL6067GY-15 Bollard 800mm OPAL GREY IP64 100-240VAC 10W 6500K 
- SL6067CH-21 Bollard 800mm CHARCOAL IP64 100-240VAC 10W 3000K 
- SL6067CH-17 Bollard 800mm CHARCOAL IP64 100-240VAC 10W 4000K 
- SL6067CH-15 Bollard 800mm CHARCOAL IP64 100-240VAC 10W 6500K 

