

Superlight Pillar LED Bollard Series

Superlight Pillar LED Bollard is designed for general purpose garden and landscape lighting applications. The Pillar bollard is a GU10 light fitting which works perfectly with the Superlight SL2210 GU10 LED module. Superlight Pillar is available in a 500mm or 700mm height options and can be supplied in Black or Grey.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	Max 10W
Profile Dimensions:	80x80mm
Height Options:	500/700mm
LED Lamp Type:	GU10
LED Lamp Compatibility:	Suits Superlight SL2210 LED Lamp
Colour/Finishes:	Matt Black / Matt Grey
Fixture Material:	Extruded Alloy
Included Accessories:	-10 ~ +50°C
IP Protection Rating:	IP55

PHOTOMETRIC INFORMATION

- SL2210-21 Warm White ● CCT 3000K CRI →85
- SL2210-17 Neutral White ● CCT 4000K CRI →85
- SL2210-15 Cool White ● CCT 6000K CRI →85

**Superlight Pillar Bollard is compatible with SL2210 GU10 LED

TYPICAL APPLICATIONS

Apartment complexes, garden & landscape lighting, public spaces, pathways, parks, driveways.

CONTROL & DIMMING COMPATIBILITY

Superlight Pillar Bollard is compatible with SL2210 GU10 LED
SL2210 GU10 LED is dimmable via most universal style 240V dimmers inc Clipsal/HPM/Dynalite

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Fixture height can be customised by special request
Colour can be refinished by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL6070BK500 Superlight Pillar LED Bollard 100-240VAC 500mm Black
- SL6070GY500 Superlight Pillar LED Bollard 100-240VAC 500mm Grey
- SL6070BK700 Superlight Pillar LED Bollard 100-240VAC 700mm Black
- SL6070GY700 Superlight Pillar LED Bollard 100-240VAC 700mm Grey

** Specify with compatible SL2210 LED lamp

** Colour temperature 3000K/4000K/6000K

