

## Superlight DL65 Commercial LED Downlight Fixture

Superlight DL65 Series is a high quality commercial downlight fixture that incorporates a high performance Zhaga LED module. The series is designed with high performance low-glare reflector and advanced LED optics. The fittings are available in a wide range of beam angle options and other configuration options.

### SPECIFICATIONS

Input Voltage:	110-240VAC
Power Consumption:	18W / 25W / 35W
Downlight Configuration:	Tilt Adjustable
Trim Diameter:	205mm
Ceiling Cutout:	185mm
LED Classification:	Zhaga LED Module
Colour/Finish:	White Trim with Silver Reflector
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	→95 High CRI Version
Beam Angle Options:	16° / 24° / 40°
Optional Accessories:	DALI Dimmable LED Driver
Recommended Ambient Temperature:	-10°-40°C
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

- SL65 Series CCT: 6500K CRI: →95 (High CRI Version) ●
- SL65 Series CCT: 4200K CRI: →95 (High CRI Version) ●
- SL65 Series CCT: 3200K CRI: →95 (High CRI Version) ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Typical applications include commercial spaces, galleries, museums, hospitality, offices, airports, retail shopping centres etc.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CUSTOMIZATION OPTIONS

Specific CCT colour temperature by special request

Customisable beam angles available by special request

DALI dimmable LED driver available by special request

\*\*Minimum order quantities apply for custom options

### ORDERING INFORMATION

- SL6518 Superlight DL65 Series LED Downlight 18W
- SL6525 Superlight DL65 Series LED Downlight 25W
- SL6535 Superlight DL65 Series LED Downlight 35W

\*\* Specify CCT 3200K / 4200K / 6500K

\*\* Specify Beam angle: 16° / 24° / 40°

