

SL7654 SIDEVIEW FLEXIBLE STRIP

Superlight Weatherproof Sideview LED Flexible Strip is a discrete LED strip product with side-emitting LED orientation. The product is ideal for curved joinery and other projects that require a side emitting light source. It is rated to IP67 for all outdoor and wet area applications.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption (per mtr):	9W
LED Quantity (per mtr):	120
LED Classification:	335 Sideview SMD
Viewing Angle:	120°
Standard Length:	Superlight can supply any length
Operating Temperature:	-5 ~ +55°C
Maximum Single Length:	10mtrs
Strip Dimensions:	11mm x 4.5mm
IP Protection Rating:	IP65
3M Mounting Tape:	Yes

PHOTOMETRIC INFORMATION

- SL7654-11 Typical Wavelength: RED 650nm
- SL7654-12 Typical Wavelength: GREEN 540nm
- SL7654-13 Typical Wavelength: BLUE 455nm
- SL7654-15 CCT: 6500K CRI: →85
- SL7654-21 CCT: 3200K CRI: →90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include outdoor commercial and residential projects, decorative lighting, backlighting & signage. IP67 rated for outdoor applications and wet areas.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

LED dimming and control options include:
Superlight DMX, DALI or 1-10V Analogue Controller
SL5041 Touch-Dim LED Dimmer

CUSTOMIZATION OPTIONS

Superlight can supply customised lengths

ORDERING INFORMATION

- SL7654-11 IP67 335 SMD Sideview LED Strip 9W 12VDC RED ●
- SL7654-12 IP67 335 SMD Sideview LED Strip 9W 12VDC GREEN ●
- SL7654-13 IP67 335 SMD Sideview LED Strip 9W 12VDC BLUE ●
- SL7654-15 IP67 335 SMD Sideview LED Strip 9W 12VDC COOL WHITE ●
- SL7654-21 IP67 335 SMD Sideview LED Strip 9W 12VDC WARM WHITE ●

Product specifications & details are subject to change without notice.

