

## Superlight SL800U Gunmetal LED Spotlight/Projector

The Superlight Gunmetal series is a professional range of LED lighting fixtures which for use within commercial projects, architectural illumination and landscapes. SL800U features a stylish design, robust construction and adjustable mounting bracket. LED configurations include options up 30W and several other configuration options are available.

### SPECIFICATIONS

Series Model Number:	SL800UA-	SL800UD-
Input Voltage:	100-240VAC	24VDC
Power Consumption:	60W/86W	60W/86W
Body Diameter:	220mm	220mm
Body Length:	200mm	200mm
Overall Height:	320mm	320mm
Fixture Material:	Magnesium Alloy	Magnesium Alloy
LED Classification:	CREE XP-E	CREE XP-E
Typical Light Source Efficacy:	90lm/W	90lm/W
Beam Angle Options:	5° / 15° / 30° / 45°	5° / 15° / 30° / 45°
RGB Option:	Int DMX Decoder	Int DMX Decoder
Recommended Ambient Temperature:	-15 ~ +55°C	-15 ~ +55°C
IK Impact Protection Rating:	→IK08	→IK08
IP Protection Rating:	IP66	IP66

### PHOTOMETRIC INFORMATION

- SL800U\*\*6500K CCT: 6500K CRI: →85 
- SL800U\*\*4000K CCT: 4000K CRI: →85 
- SL800U\*\*3000K CCT: 3000K CRI: →85 
- SL800U\*\*RGB RGB with DMX 

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Typical applications include landscape and feature lighting, sculptures and flagpole illumination, garden lighting and architectural highlighting.

### CONTROL & DIMMING COMPATIBILITY

Superlight SL800 fittings can be fitted with integral dimming control gear by special request. RGB+DMX configuration available. RGB fitting is supplied with integral DMX decoder.

### CUSTOMIZATION OPTIONS

Fixture colour can be refinished

DALI dimmable options available by special request

Y-Bracket (yoke) mounting option available by special request

Vandal resistant protective steel cage available by special request

Custom options may be subject to minimum order quantities

### ORDERING INFORMATION

- SL800U\*\*-3000K Superlight SL600U LED Landscape Spotlight/Projector
- SL800U\*\*-4000K Superlight SL600U LED Landscape Spotlight/Projector
- SL800U\*\*-6500K Superlight SL600U LED Landscape Spotlight/Projector
- SL800U\*\*-RGB Superlight SL600U LED Landscape Spotlight/Projector

\*\*Specify LED configuration 60W/86W

\*\*Specify input voltage option 100-240VAC or 24VDC

\*\*Specify beam angle option 5° / 12° / 15° / 20° / 30° / 45°

