

## SL8608 Superlight Quadstrip LED Striplight

Superlight Quadstrip is special purpose LED light source, especially designed for use in larger Superlight mounting profiles. The product features precise LED array and spacing to ensure superior uniformity and smooth lighting effects when used as feature lighting within a mounting profile and opal lens diffuser.

### SPECIFICATIONS

Input Voltage:	24VDC
Power Consumption:	26W per mtr
Dimensions:	36mm Width
LED Classification:	SSC SMD LED
Colour/Finish:	White PCB
Typical Light Source Efficacy:	→95lm/W
Light Source Viewing Angle:	120°
Mounting Method:	3M 230 Mounting Tape
Standard Length:	Superlight can supply any length
Max Single Length	5mtrs
Heatsink Required? Yes:	Use HLP Mounting Profile
Recommended Ambient Temperature:	-5 ~ +55°C
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

• SL8608-15	Superlight LED Quadstrip	CCT: 6500K	CRI: →90	●
• SL8608-17	Superlight LED Quadstrip	CCT: 4200K	CRI: →90	●
• SL8608-21	Superlight LED Quadstrip	CCT: 3200K	CRI: →90	●
• SL8608-27	Superlight LED Quadstrip	CCT: 2700K	CRI: →90	●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

LED Quadstrip is specifically designed for use in Superlight HLP profiles to provide a complete high performance lighting solution. Suitable for use in demanding commercial projects for task lighting, backlighting, general area lighting and specialist lighting projects.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CUSTOMIZATION OPTIONS

Superlight can manufacture any required lengths  
Compatible with Superlight DMX521, DALI and 1-10V Controllers  
Can be supplied complete with matching mounting profile

### ORDERING INFORMATION

• SL8608-15	●	Superlight LED Quadstrip 24VDC 26W per mtr 6500K
• SL8608-17	●	Superlight LED Quadstrip 24VDC 26W per mtr 4200K
• SL8608-21	●	Superlight LED Quadstrip 24VDC 26W per mtr 3200K
• SL8608-27	●	Superlight LED Quadstrip 24VDC 26W per mtr 2700K

