

Superlight DL86 Commercial LED Downlight Fixture

Superlight DL86 Series is a high quality commercial downlight fixture that incorporates a high performance Zhaga LED module. The series is designed with high performance low-glare reflector and advanced LED optics. The fittings are available in a wide range of beam angle options and other configuration options.

SPECIFICATIONS

Input Voltage:	110-240VAC
Power Consumption:	24W / 35W / 60W
Downlight Configuration:	Wall Washer
Trim Diameter:	258mm
Ceiling Cutout:	236mm
LED Classification:	Zhaga LED Module
Colour/Finish:	White Trim with Silver Reflector
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	→95 (High CRI Version)
Beam Angle Options:	16° / 24° / 40°
Optional Accessories:	DALI Dimmable LED Driver
Recommended Ambient Temperature:	-10°-40°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

- SL86 Series CCT: 6500K ● CRI: →95 (High CRI Version)
- SL86 Series CCT: 4200K ● CRI: →95 (High CRI Version)
- SL86 Series CCT: 6500K ● CRI: →95 (High CRI Version)

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include commercial spaces, galleries, museums, hospitality, offices, airports, retail shopping centres etc.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Specific CCT colour temperature by special request

Customisable beam angles available by special request

DALI dimmable LED driver available by special request

* Minimum order quantities apply for custom options

ORDERING INFORMATION

- SL8624 Superlight DL86 Series LED Downlight 16W
- SL8635 Superlight DL86 Series LED Downlight 35W
- SL8660 Superlight DL86 Series LED Downlight 60W

** Specify CCT 3200K / 4200K / 6500K

** Specify Beam Angle: 16° / 24° / 40°

