


SL9621 OPTO-21 HIGH POWER LED PROJECTOR

The Opto-21 is a high-quality LED floodlight fitting suitable for indoor & outdoor illumination. The Opto-21 has a very compact body making it suitable for all small to medium floodlighting & wall-washing projects.

SPECIFICATIONS

Input Voltage:	24VDC
Standard Dimensions (L x W x H):	348 x 80 x 125mm
Max Power Consumption (Watts):	21W
LED Quantity:	6 (700mA)
LED Classification:	3.5W High Power Tri-Chip RGB LED
Operating Temperature:	-5°C ~ +55°C
Standard Beam/Viewing Angle:	22°
No of Possible Defined Colours:	16.7 Million + (RGB Version)
Potential Illumination Distance:	30-45mtrs
Face Diameter:	120mm
Overall Height:	170mm
Colour Control Via:	Use Any Superlight RGB Controller
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

- SL9621-35 RGB Colour Controllable 

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include landscape-lighting, bars & nightclubs, architectural lighting, stage lighting, hotels, plazas, corporate colour-theming, wall & feature illumination etc.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

RGB CONTROL OPTIONS

Superlight DMX512, DALI, Analogue 1-10V Protocol
Superlight Stand alone RGB controller

CUSTOMIZATION OPTIONS

Fixture colour can be refinished
Customised bracket available by special request
Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

- SL9621-35 24VDC Opto-21 High Output LED Floodlight RGB 