

Superlight SL500-15D Gunmetal LED Landscape Fixture

The Superlight Gunmetal series is a professional range of LED lighting fixtures which for use within commercial projects, architectural illumination and landscapes. SL500 features a stylish design, robust construction and adjustable mounting bracket or yoke-mount option.

SPECIFICATIONS

Series Model Number:	SL500Y15D	SL500U15D
Mounting Bracket:	Y Bracket	U Bracket
Input Voltage:	90-265VAC	90-265VAC
Power Consumption:	28W	28W
Face Dimensions:	362x127	362x127
Body Depth:	146mm	146mm
Overall Height:	165mm	165mm
Fixture Material:	Magnesium Alloy	Magnesium Alloy
LED Classification:	CREE XP LED	CREE XP LED
LED Qty:	15	15
Typical Light Source Efficacy:	90lm/W	90lm/W
Beam Angle Options:	6° / 15° / 30° / 48°	6° / 15° / 30° / 48°
RGB Option:	24VDC with DMX512	24VDC with DMX512
Recommended Ambient Temperature:	-15 ~ +55°C	-15 ~ +55°C
IK Impact Protection Rating:	→IK08	→IK08
IP Protection Rating:	IP66	IP66

PHOTOMETRIC INFORMATION

- SL500*15D-6500K CCT: 6500K CRI: →85 
- SL500*15D-4000K CCT: 4000K CRI: →85 
- SL500*15D-3000K CCT: 3000K CRI: →85 
- SL500*15D-RGB RGB 24VDC with DMX 

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include landscape and feature lighting, sculptures and flagpole illumination, garden lighting and architectural highlighting.

CONTROL & DIMMING COMPATIBILITY

Superlight SL500 fittings can be fitted with integral dimming control gear by special request. RGB+DMX configuration available. RGB fitting is supplied with integral DMX decoder.

CUSTOMIZATION OPTIONS

Fixture colour can be refinished

DALI dimmable options available by special request

Vandal resistant protective steel cage available by special request

Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL500*15D-3000K Superlight SR500 LED Landscape Spotlight/Projector
- SL500*15D-4000K Superlight SR500 LED Landscape Spotlight/Projector
- SL500*15D-6500K Superlight SR500 LED Landscape Spotlight/Projector
- SL500*15D-RGB Superlight SR500 LED Landscape Spotlight/Projector

**Specify mounting bracket type: Y Bracket or U Bracket

**Specify input voltage option: 100-240VAC or 24VDC (RGB Option)

**Specify beam angle option: 6° / 15° / 30° / 48°

