

Superlight VTN Linear LED Batten Fixture

Superlight VTN is a professional LED batten fixture suitable for general purpose use. It is simple to install and is an ideal replacement for traditional fluorescent battens. Powered using high efficiency LED technology and integral control gear, VTN features a durable polycarbonate diffuser which provides excellent uniformity.

SPECIFICATIONS

Series Part Number:	VTN Series
Input Voltage:	100-240VAC
Power Consumption:	Various Wattage Options 10W-24W
Nominal Fixture Lengths:	Various Length Options 640mm-1575mm
Profile Dimensions:	60(w)x53(h)mm
Fixture Material:	Polycarbonate
LED Classification:	SMD2835 LED
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	→85
Beam Angle:	120°
Power Factor:	→0.9
Recommended Ambient Temperature:	-10 ~ +40°C
Minimum IK Protection Rating:	IK08
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

- VTN CCT: 6500K CRI: →90 ●
- VTN CCT: 5000K CRI: →90 ●
- VTN CCT: 4000K CRI: →85 ●
- VTN CCT: 3000K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General purpose commercial lighting, industrial lighting projects, utility lighting, storerooms, garages, work spaces, common areas, corridors, carparks.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Optional DALI dimmable version is available by special request

CUSTOMIZATION OPTIONS

Superlight can supply custom configurations to suit specific applications. Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- | | |
|-----------|---|
| • SL7582 | VTN Linear Diffused LED Batten IP20 100-240VAC 582mm 10W |
| • SL7758 | VTN Linear Diffused LED Batten IP20 100-240VAC 758mm 12W |
| • SL7908 | VTN Linear Diffused LED Batten IP20 100-240VAC 908mm 15W |
| • SL71192 | VTN Linear Diffused LED Batten IP20 100-240VAC 1192mm 20W |
| • SL71575 | VTN Linear Diffused LED Batten IP20 100-240VAC 1575mm 24W |

**Specify CCT option: 3000K/4000K/5000K/6000K

