

Superlight VTN-D Linear LED Batten Fixture

Superlight VTN-D is a wider body professional LED batten fixture suitable for general purpose use. It is simple to install and is an ideal replacement for traditional fluorescent battens. Powered using high efficiency LED technology and integral control gear, VTN-D features a durable polycarbonate diffuser which provides excellent uniformity.

SPECIFICATIONS

Series Part Number:	VTN-D Series
Input Voltage:	100-240VAC
Power Consumption:	Various Wattage Options 20W-80W
Nominal Fixture Lengths:	Various Length Options 585mm-2372mm
Profile Dimensions:	81(w)x50(h)mm
Fixture Material:	Polycarbonate
LED Classification:	SMD2835 LED
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	→85
Beam Angle:	120°
Power Factor:	→0.9
Emergency Configuration	2HR Emergency Version Available by Request
Recommended Ambient Temperature:	-10 ~ +40°C
Minimum IK Protection Rating:	IK08
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

- VTN-D CCT: 6500K CRI: →90 ●
- VTN-D CCT: 5000K CRI: →90 ●
- VTN-D CCT: 4000K CRI: →85 ●
- VTN-D CCT: 3000K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General purpose commercial lighting, industrial lighting projects, utility lighting, storerooms, garages, work spaces, common areas, corridors, carparks.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Optional DALI dimmable version is available by special request

CUSTOMIZATION OPTIONS

2HR Emergency Lighting Option Available

Custom lengths available by special request

Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL7585D VTN-D Linear Diffused LED Batten 100-240VAC 585mm 20W
- SL7758D VTN-D Linear Diffused LED Batten 100-240VAC 758mm 24W
- SL7908D VTN-D Linear Diffused LED Batten 100-240VAC 908mm 30W
- SL71192D VTN-D Linear Diffused LED Batten 100-240VAC 1192mm 40W
- SL71498D VTN-D Linear Diffused LED Batten 100-240VAC 1498mm 48W
- SL71798D VTN-D Linear Diffused LED Batten 100-240VAC 1798mm 60W
- SL72372D VTN-D Linear Diffused LED Batten 100-240VAC 2372mm 80W

**Specify CCT option: 3000K/4000K/5000K/6500K

