

SUPERLIGHT FL7060 LED FLOODLIGHT - 60W

Superlight FL7 is a new generation LED floodlight with integrated mains voltage LED module. FL7 delivers superior lumen output with optimum efficiency. The fittings are manufactured from robust materials and can be used in any Industrial, commercial or residential environment.

SPECIFICATIONS

Input Voltage:	85-285VAC
Max Power Consumption:	60W
Dimensions:	280x220x113mm
Colour/Finish:	Black / Corrosion Resistant
Electrical Insulation Class:	Class I
Light Source Classification:	Osram 3030T
Construction Material:	Aluminium
Recommended Ambient Temp:	-20°C ~ 50°C
IP Protection Rating:	IP65
Minimum IK Rating:	IK09
Dimmable:	Yes

PHOTOMETRIC INFORMATION

- FL7060 CCT: 6500K CRI: →80 ●
- FL7060 CCT: 4000K CRI: →80 ●
- FL7060 CCT: 3000K CRI: →80 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Ideally suited for high end washing applications such as nightclubs wall-washing, architectural lighting, hotels, plazas, corporate colour-schemes, special events, venues & productions etc.

3D Modelling & Lighting Design

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Non standard colours available by special request
DALI dimmable version available by special request
Also available in 80W configuration

ORDERING INFORMATION

- FL7060 Superlight LED Floodlight - 3000K ●
- FL7060 Superlight LED Floodlight - 4000K ●
- FL7060 Superlight LED Floodlight - 6500K ●

