

SL2150 NX-150R RECESSED LED DOWNLIGHT

Superlight Nexus LED Downlights are high quality LED fixtures that combine high powered Sharp LED technology with excellent architectural light fixture design. The fittings have an integrated polycarbonate lens assembly and semi-polished reflector for optimum performance.

The NX-150R/26W model suits 150mm ceiling cutouts and incorporates Sharp 26W LED. Optional 18W LED version available by request.

SPECIFICATIONS

Input Voltage:	110-240VAC
Max Power Consumption:	26Watts
LED Quantity:	1
LED Classification:	Sharp High Power
Standard Beam Angle:	60°
LED Drive Current:	700mA
IP Rating:	IP44
Physical Dimensions:	Trim: 170mm Ceiling Cutout: 150mm
Minimum Ceiling Depth Required:	120mm
Dimmable:	Yes
Recommended Ambient Temp:	-20 ~ +45°C

CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

Residential Application	Ceiling Height: 3.0m-5.0m
Commercial Application	Ceiling Height: 2.7m-5.0m

PHOTOMETRIC INFORMATION

- SL2150-21 Warm White ● CCT 3000K CRI →83
- SL2150-17 Neutral White ● CCT 4200K CRI →86
- SL2150-15 Cool White ● CCT 5500K CRI →85

TYPICAL APPLICATIONS

High-end commercial & residential installations, luxury properties & hotel fitouts, retail environments, shopping centres, commercial common areas offices spaces, laboratory & medical projects, airports etc.

CUSTOMIZATION OPTIONS

Fitting colour can be refinished by request
Can be fitted with lower power 18W Sharp LED
Optional Dali Dimmable
Minimum order quantity applies for custom options

ORDERING INFORMATION

- SL2150-15 Nexus 150R LED Downlight 26W Cool White 5500K ●
- SL2150-21 Nexus 150R LED Downlight 26W Warm White 3000K ●
- SL2150-17 Nexus 150R LED Downlight 26W Neutral White 4200K ●

