

SL2278 MINI LED DOWNLIGHT ROUND

Superlight Mini LED downlights are suitable for applications where a small fitting is required, such as joinery & furniture lighting, marine applications, discrete architectural lighting, kitchen & bathroom lighting etc.

The mini LED downlight has excellent light output thanks to the powerful CREE 3W LED. The fittings can be either recessed or surface-mounted using the optional surface-mount base.

SPECIFICATIONS

| | |
|-------------------------------|--------------------------------|
| Input Voltage: | 12VDC |
| Max Power Consumption(Watts): | 3W |
| LED Classification: | High Power Cree 3W |
| Colour Temperature (cw/ww): | 6500K/3200K |
| Beam Angles Available: | 30° or 60° |
| Mounting Options: | Recessed or Surface Mount |
| Trim Dimensions: | 33 mm |
| Fixture Depth: | 22mm |
| Operating Temperature: | -5 ~ +55°C |
| Dimmable: | Yes with Superlight LED Dimmer |

PHOTOMETRIC INFORMATION

- SL2278-15 CCT: 6500K CRI: →85 ●
- SL2278-21 CCT: 3200K CRI: →90 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Joinery & Furniture Lighting, Marine Applications, Discrete architectural lighting, Kitchen & bathroom lighting etc.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

LED DRIVER COMPATIBILITY

Superlight constant voltage 12VDC LED Driver.

CUSTOMIZATION OPTIONS

Trim colour can be refinished

30° or 60° lens options

Customisation options are subject to availability and minimum order quantities.

ORDERING INFORMATION

- SL2278-15 Round 3W Mini LED Downlight 30° 6500K COOL WHITE ●
- SL2278-21 Round 3W Mini LED Downlight 30° 3200K WARM WHITE ●
- SL2279-15 Round 3W Mini LED Downlight 60° 6500K COOL WHITE ●
- SL2279-21 Round 3W Mini LED Downlight 60° 3200K WARM WHITE ●

