

SL2281 LED CLIPPER CEILING LIGHT 118MM 8W

Superlight LED Clipper light fittings are modern and stylish general purpose surface mounted LED ceiling fittings. They are an ideal LED alternative to oyster lights and other conventional ceiling light fittings.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	8W
LED Drive Current:	500mA
LED Classification:	SMD 3528
Beam Angle:	120°
Standard Length:	Superlight can supply any length
Dimmable:	Yes
Dimensions Depth:	39mm
Dimensions Diameter:	117mm
IP Rating:	IP44
Recommended Operating Temp:	-5 ~ +55°C

PHOTOMETRIC INFORMATION

• SL2281-15	CCT: 6500K	CRI: →80	●
• SL2281-17	CCT: 4200K	CRI: →85	●
• SL2281-21	CCT: 3200K	CRI: →85	●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include commercial and residential projects, decorative lighting, backlighting

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Superlight LED Clipper fittings are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

CUSTOMIZATION OPTIONS

Fitting colour can be refinished
Remote mounted DALI dimmable driver available by request
Superlight can also manufacture square body by special request
Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

• SL2281-15	Superlight LED Clipper 8W 117mm 6500K COOL WHITE	●
• SL2281-17	Superlight LED Clipper 8W 117mm 4200K NEUTRAL WHITE	●
• SL2281-21	Superlight LED Clipper 8W 117mm 3200K WARM WHITE	●

Product specifications & details are subject to change without notice.

