

SL2284 LED CLIPPER CEILING LIGHT 300MM 30W

Superlight LED Clipper light fittings are modern and stylish general purpose surface mounted LED ceiling fittings. They are an ideal LED alternative to oyster lights and other conventional ceiling light fittings.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	30W
LED Drive Current:	1000mA
LED Classification:	SMD 3528
Beam Angle:	120°
Standard Finish:	Matt White
Dimmable:	Yes
Dimensions Depth:	39mm
Dimensions Diameter:	300mm
IP Rating:	IP44
Recommended Operating Temp:	-5 ~ +55°C

PHOTOMETRIC INFORMATION

- SL2284-15 CCT: 6500K CRI: →80 ●
- SL2284-17 CCT: 4200K CRI: →85 ●
- SL2284-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General area lighting in commercial and residential applications, Retrofit replacement for existing oyster style light fittings

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Superlight LED Clipper fittings are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

CUSTOMIATION OPTIONS

Fitting colour can be refinished

Remote mounted DALI dimmable driver available by request

Superlight can also manufacture square body by special request

Customisation options are subject to availability and minimum order quantities

ORDERING INFORMATION

- SL2284-15 Superlight LED Clipper 11W 180mm 6500K COOL WHITE ●
- SL2284-17 Superlight LED Clipper 11W 180mm 4200K NEUTRAL WHITE ●
- SL2284-21 Superlight LED Clipper 11W 180mm 3200K WARM WHITE ●

