

SL2290 13W Compact LED Downlight Fitting

Superlight SL2290 Compact LED Downlight fittings are revolutionary in their fixture design and performance. With an extremely compact slimline design, they are ideal for projects with very limited ceiling depth. The fittings are supplied complete with Superlight dimmable LED driver.

SPECIFICATIONS

Driver Input Voltage:	240VAC
Max Power Consumption:	13 Watts
LED Quantity:	Single 13W MV-X LED
LED Classification:	High Power MV-X 13W (700mA)
Drive Current:	Constant Current
Standard Beam Angle:	60° Wide Beam
Colour Temp (CW/WW)	6500K/3200K
Physical Dimensions:	Trim:105mm Cutout:90mm
Minimum Ceiling Depth Required:	35mm Depth - Compact
Dimmable:	Yes (dimmable driver included)
Operating Temperature:	-5 ~ +55°C

PHOTOMETRIC INFORMATION

- SL2290-15 CCT: 6500K CRI: →80 ●
- SL2290-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General lighting in residential projects with very low ceiling depth, Retro-fitting of existing halogen style LED downlights.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

Residential Application Ceiling Height: 2.4m-3.4m

CONTROL & DIMMING COMPATIBILITY

Superlight SL2290 Compact LED Downlights are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

CUSTOMIZATION OPTIONS

Trim colour can be refinished

Dali dimmable driver available by request

CCT 4200K available by request

Customisation options are subject to minimum order quantities

ORDERING INFORMATION

- SL2290-15 13W Compact LED Downlight 6500K COOL WHITE ●
- SL2290-21 13W Compact LED Downlight 3200K WARM WHITE ●

