

SL2391 LED DOWNLIGHT ONE GANG SLOTTER

Architecturally designed LED downlight series with classical slotter design, ideally suited for high-quality residential projects & commercial fit-outs. The slotter design incorporates individually adjustable LED apertures which provide optimum use flexibility.

SPECIFICATIONS

Input Voltage:	220-240VAC
Max Power Consumption:	13Watts
LED Quantity:	1
LED Classification:	High Power MV-LED
Standard Beam Angle:	45°
LED Drive Current:	350mA
IP Rating:	IP20
Trim Dimensions:	Trim: 108 x 108mm
Ceiling Cutout:	Cutout: 95 x 95mm
Minimum Ceiling Depth Required:	92mm
Standard Trim Finish:	Matt White
LED Lens:	Polycarbonate
Dimmable:	Yes
Recommended Ambient Temp:	-20 ~ +45°C

CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

Residential Application	Ceiling Height: →3.5m
Commercial Application	Ceiling Height: 3.0m-5.5m

PHOTOMETRIC INFORMATION

- SL2391-21 Warm White ● CCT 3000K CRI →85
- SL2391-17 Neutral White ● CCT 4000K CRI →85
- SL2391-15 Cool White ● CCT 6000K CRI →80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include residential projects, retail showrooms, shopping centres, galleries, offices, restaurants, cafes & hospitality projects, food preparation areas.

CUSTOMIZATION OPTIONS

- Trim colour can be refinished
- Metallic trim finishes available by request
- Matching two-gang & three-gang versions also available

ORDERING INFORMATION

- SL2391-21 Slotter 1-Gang LED Downlight White Trim 3000K ●
- SL2391-17 Slotter 1-Gang LED Downlight White Trim 4000K ●
- SL2391-15 Slotter 1-Gang LED Downlight White Trim 6000K ●

