

## SL2692 Multigang LED Downlight Series

Superlight SL2692 is a square adjustable LED downlight with a discrete design and high quality LED light source. The fitting is supplied with dimmable LED driver and can be used for residential or commercial projects. This Multigang series is available in one, two and three-gang versions.

### SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	20W
Trim Dimensions:	110x200mm
Ceiling Cutout:	90x180mm
Fitting Depth:	63mm
LED Classification:	Sharp COB
LED Quantity:	2x10W
LED Drive Current:	470mA
Typical Light Source Efficacy:	90lm/W
Beam Angle Options:	60°
Recommended Ambient Temperature:	-10 ~ +45°C
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

- SL2692-15 CCT: 5000K CRI: →90 ●
- SL2692-17 CCT: 4000K CRI: →90 ●
- SL2692-21 CCT: 3000K CRI: →90 ●
- SL2692-27 CCT: 2700K CRI: →90 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Residential downlighting, corridors and foyers, hotels and hospitality projects, residential developments, display cases, architectural projects, retail and showrooms, hotels, reception areas, waiting rooms, offices and commercial fitouts.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CONTROL & DIMMING COMPATIBILITY

Superlight Multigang LED downlights are supplied with phase control dimmable LED drivers  
Optional DALI dimmable LED driver is available by special request  
Optional 1-10V dimmable LED driver is available by special request

### CUSTOMIZATION OPTIONS

Fixture trim can be refinished by special request  
Inner module colour can be refinished - two tone colour options

\*\*Custom options may be subject to minimum order quantities

### ORDERING INFORMATION

- SL2692-27 Multigang LED Downlight 2-Gang 110x200mm 60° 20W 2700K ●
- SL2692-21 Multigang LED Downlight 2-Gang 110x200mm 60° 20W 3000K ●
- SL2692-17 Multigang LED Downlight 2-Gang 110x200mm 60° 20W 4000K ●
- SL2692-15 Multigang LED Downlight 2-Gang 110x200mm 60° 20W 5000K ●

