

## SL2765 IP65 Recessed LED Downlight

The Superlight SL2765 is an IP65 recessed LED downlight that is suitable for harsh environments or wet areas. The fitting features a high integrity rubber gasket seal and IP65 cable gland to offer the maximum protection from water ingress. SL2765 is suitable for all commercial and residential applications.

### SPECIFICATIONS

Driver Input Voltage:	100-240VAC
Max Power Consumption:	15W
Trim Diameter:	95mm
Ceiling Cutout:	80-90mm
Fitting Depth:	77mm
LED Classification:	Sharp COB LED
Materials:	Aluminium Alloy 1090
Typical Light Source Efficacy:	100lm/W
LED Beam Angle:	55°
LED Driver Power Factor:	→0.85
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP65

### PHOTOMETRIC INFORMATION

- SL2765-15 CCT: 6000K CRI: →90 ●
- SL2765-17 CCT: 4000K CRI: →90 ●
- SL2765-21 CCT: 3200K CRI: →90 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Outdoor lighting, harsh environments, awnings and soffits, residential projects, retail and shopfitting projects, common areas, general purpose lighting, kitchen lighting, commercial spaces, work environments.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CONTROL & DIMMING COMPATIBILITY

Superlight SL2765 LED downlights are supplied with phase control dimmable LED drivers  
Optional DALI dimmable LED driver is available by special request  
Optional 1-10V dimmable LED driver is available by special request

### CUSTOMIZATION OPTIONS

Fixture trim can be refinished by special request

\*\*Custom options may be subject to minimum order quantities

### ORDERING INFORMATION

- SL2765-21 Superlight IP65 Recessed LED Downlight 15W 3200K ●
- SL2765-17 Superlight IP65 Recessed LED Downlight 15W 4000K ●
- SL2765-15 Superlight IP65 Recessed LED Downlight 15W 6000K ●

