

SL2915 ECO-15 RECESSED LED DOWNLIGHT

EC015 LED Downlights from Superlight combine high power LED technology with a high end architectural fixture design to provide an exceptional downlight fixture for any residential or commercial project. The EC015 LED Downlights have a high LED position which provides an anti-glare feature and unique aesthetic finish. EC015 LED downlights come complete with a Superlight dimmable driver and have a wide 60° beam angle making them ideal for all general ceiling downlighting applications.

SPECIFICATIONS

Driver Input Voltage:	240VDC
Max Power Consumption:	15 Watts
LED Quantity:	1 x 15W Sharp LED
LED Classification:	High Power Sharp MV-X 15W
Drive Current:	680mA
Standard Beam Angle:	60° Wide Beam
Colour Temp (cool-white/warm-white)	6000K/3000K
Physical Dimensions:	Trim:100mm Cutout:90mm
Minimum Ceiling Depth Required:	115mm
Dimmable With Standard Dimmers:	Yes (dimmable driver included)
Operating Temperature:	-5 ~ +55°C

PHOTOMETRIC INFORMATION

- SL2915-15 CCT: 6500K CRI: →80 ●
- SL2915-17 CCT: 4200K CRI: →85 ●
- SL2915-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

High end architectural projects
Retro-fitting of existing 90mm downlights

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

Residential Application	Ceiling Height: 2.4m-3.7m
Commercial Application	Ceiling Height: 2.4m-3.7m

CONTROL & DIMMING COMPATIBILITY

EC015 LED downlights are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

CUSTOMIZATION OPTIONS

Fitting can be refinished in black by request
Dali dimmable driver available by request
Customisation options are subject to minimum order quantities

ORDERING INFORMATION

- SL2915-15 ECO15 15W Adj. LED Downlight 6500K COOL WHITE ●
- SL2915-17 ECO15 15W Adj. LED Downlight 4200K NEUTRAL WHITE ●
- SL2915-21 ECO15 15W Adj. LED Downlight 3200K WARM WHITE ●

