

Superlight SL2939 Recessed LED Downlight

Superlight SL2939 is a low profile recessed LED downlight with centre-tilt adjustable design. The fitting integrates a high quality LED light source within an architectural fixture. Manufactured from premium materials and components, the fitting is especially suited for projects that demand a quality architectural downlight with a low profile.

SPECIFICATIONS

Driver Input Voltage:	100-240VAC
Power Consumption:	15W
Trim Diameter:	105mm
Ceiling Cutout:	95mm
Fitting Depth:	56mm
LED Classification:	CREE XR LED
LED Quantity:	1
Typical Light Source Efficacy:	90lm/W
Beam Angle:	60°
Adjustable Tilt:	30-degree Centre Tilt
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP44

PHOTOMETRIC INFORMATION

- SL2939-15 CCT: 6500K CRI: →90 ●
- SL2939-17 CCT: 4200K CRI: →90 ●
- SL2939-21 CCT: 3200K CRI: →90 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Residential downlighting, projects with restricted ceiling space, new homes, high-rise residential developments, common areas and corridors, retail fitouts, offices and commercial spaces.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Superlight SL2939 LED downlights are supplied with phase control dimmable LED drivers
Optional DALI dimmable LED driver is available by special request
Optional 1-10V dimmable LED driver is available by special request

CUSTOMIZATION OPTIONS

Fixture trim can be refinished by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL2939-21 Superlight Adjustable LED Downlight IP44 15W 3200K ●
- SL2939-17 Superlight Adjustable LED Downlight IP44 15W 4200K ●
- SL2939-15 Superlight Adjustable LED Downlight IP44 15W 6500K ●

**Specify Beam angle: 15° / 24°

