

## SL2954 SHOWER LED DOWNLIGHT IP54

Superlight SL2954 LED downlight fittings are rated to IP54 protection level which makes them ideal for installation into wet areas such as shower cubicles, public spaces, commercial applications and any location where a wet area downlight is required.

### SPECIFICATIONS

Driver Input Voltage:	240VAC
Max Power Consumption:	13 Watts
LED Quantity:	Single 13W MV-X LED
LED Classification:	High Power MV-X 13W (700mA)
Drive Current:	700mA
Standard Beam Angle:	60° Wide Beam
Colour Temp (CW/WW)	6500K/3200K
Physical Dimensions:	Trim:98mm Cutout:90mm
Minimum Ceiling Depth Required:	118mm
Dimmable:	Yes (dimmable driver included)
Operating Temperature:	-5 ~ +55°C
IP Rating:	IP54

### PHOTOMETRIC INFORMATION

- SL2954-15 CCT: 6500K CRI: →80 ●
- SL2954-21 CCT: 3200K CRI: →85 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

General lighting in shower cubicles and wet areas, Commercial kitchens and harsh environments, Wet area downlighting applications.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CEILING HEIGHT COMPATIBILITY

Residential Application	Ceiling Height: 2.4m-3.0m
Commercial Application	Ceiling Height: 2.4m-3.0m

### CONTROL & DIMMING COMPATIBILITY

Superlight SL2954 LED Downlights are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

### CUSTOMIZATION OPTIONS

Trim colour can be refinished  
Dali dimmable driver available by request  
CCT 4200K available by request  
Customisation options are subject to minimum order quantities

### ORDERING INFORMATION

- SL2954-15 IP54 Fixed Shower LED Downlight 6500K COOL WHITE ●
- SL2954-21 IP54 Fixed Shower LED Downlight 3200K WARM WHITE ●

