

SL2956 ECO18 RECESSED LED DOWNLIGHT

The Superlight ECO18 Recessed LED downlight incorporates a high power Sharp MV-X LED in a stylish & contemporary semi-trimless fixture design. ECO18 LED downlights have a wide 60° beam which is optimised for general area downlighting applications.

Each ECO18 fitting comes complete with a Superlight dimmable driver which allows smooth dimming via standard leading-edge, trailing edge and universal style dimmers.

SPECIFICATIONS

Driver Input Voltage:	240VAC
Max Power Consumption:	15Watts
LED Quantity:	1
LED Classification:	Sharp High Power
LED Drive Current:	320mA
Standard Beam Angle:	60° Beam
Physical Dimensions:	Trim: 125mm Ceiling Cutout:115mm
Minimum Ceiling Depth Required:	120mm
Dimmable:	Yes (Dimmable Driver Included)
IP Protection Rating:	IP44
Operating Temperature:	-20 ~ +55°C



CEILING HEIGHT COMPATIBILITY

Ceiling height recommendations are for general area lighting purposes.

Residential Application	Ceiling Height: 2.4m-3.7m
Commercial Application	Ceiling Height: 2.4m-3.7m

PHOTOMETRIC INFORMATION

• SL2956-21 Warm White	● CCT 3000K	CRI →90
• SL2956-17 Neutral White	● CCT 4200K	CRI →85
• SL2956-15 Cool White	● CCT 6000K	CRI →85

TYPICAL APPLICATIONS

Typical applications include high-end commercial fitouts. Retail environments, shopping centres, offices, high-end residential projects.

CUSTOMIZATION OPTIONS

Fixture colour can be refinished
Can be fitted with optional 15W,18W or 26W Sharp LED
Dali Dimmable Driver available by request
Customisation options are subject to minimum order quantities

ORDERING INFORMATION

• SL2956-15	ECO18 LED Downlight 15W	Cool White 6000K	●
• SL2956-17	ECO18 LED Downlight 15W	Neutral White 4200K	●
• SL2956-21	ECO18 LED Downlight 15W	Warm White 3000K	●