

Superlight Satellite SL2978 LED Track Spotlight

Superlight Satellite is a high quality LED light fixture suitable for track mounting. The product can be configured with a variety of versions, including different main colour, inner ring colours and also a variety of LED light source colour temperatures. The Satellite series is available with either single-circuit or three-circuit track adaptors.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	9W
Fixture Body Diameter:	50mm
Fixture Body Length:	160mm
LED Classification:	CREE XA LED
LED Quantity:	1
Colour/Finish Options:	White/Black
Inner Ring Baffle Colour Options	Aluminium Alloy
Fixture Material:	110lm/W
Typical Light Source Efficacy:	20° / 38°
Beam Angle Options:	Single Circuit/Three Circuit
Adjustable Tilt Angle:	360° Swivel / 100° Tilt
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

- SL2978* -15 CCT: 5000K CRI: →90 ●
- SL2978* -17 CCT: 4000K CRI: →90 ●
- SL2978* -21 CCT: 3000K CRI: →90 ●
- SL2978* -27 CCT: 2700K CRI: →90 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Residential and commercial interiors, task lighting, spotlighting, retail and show-room environments, galleries, museums, shopfitting projects, architectural high-lighting.

TRACK SYSTEM COMPATIBILITY

SL2978 track light series is available with either single circuit or three circuit track adaptor.

Superlight can supply complete track lighting systems including hardware and accessories.

CUSTOMIZATION OPTIONS

Fixture colour available in WHITE or BLACK

Other fixture colours available by special request

Inner ring colour options include GOLD, WHITE or BLACK

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- Series Model Number: SL2978

**Specify beam angle: 20° / 38°

**Specify fixture colour: WHITE/BLACK

**Specify inner ring colour: WHITE/BLACK/GOLD

**Specify track adaptor: SINGLE CIRCUIT/THREE CIRCUIT

