

Superlight Revo-XR26 Recessed LED Downlight

Superlight Revo-XR26 is a quality LED downlight fitting suitable for high-end interior projects. The fitting features an internal polished specular reflector with integrated LED light source which delivers superior optical performance and aesthetic.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	26W
Trim Diameter:	175mm
Ceiling Cutout:	165mm
Fixture Depth:	130mm
LED Classification:	Single 26W Sharp MX-V LED
Reflector Configuration:	Semi-Specular Polished Reflector
Typical Light Source Efficacy:	110lm/W
LED Light Source CRI:	→90
Beam Angle:	60°
Power Factor?	→0.9
Recommended Ambient Temperature:	-5 ~ +55°C
IP Protection Rating:	IP44



PHOTOMETRIC INFORMATION

- SL2968-15 CCT: 6000K CRI: →90 ●
- SL2986-17 CCT: 4000K CRI: →90 ●
- SL2986-21 CCT: 3200K CRI: →90 ●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

High-end residential decors, commercial projects, retail showrooms, hotels and hospitality projects, common areas, office fitouts, malls and galleries, airports, education and government projects.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CONTROL & DIMMING COMPATIBILITY

Superlight Revo-XR26 LED downlights are supplied with phase control dimmable LED drivers
Optional DALI dimmable LED driver is available by special request
Optional 1-10V dimmable LED driver is available by special request

CUSTOMIZATION OPTIONS

Trim fixture can be refinished by special request
Optional DALI dimmable version by special request

**Custom options may be subject to minimum order quantities

ORDERING INFORMATION

- SL2986-15 Superlight Revo-XR26 LED Downlight Dimmable Driver 3200K ●
- SL2986-17 Superlight Revo-XR26 LED Downlight Dimmable Driver 4000K ●
- SL2986-21 Superlight Revo-XR26 LED Downlight Dimmable Driver 6000K ●