

## Superlight SL3054 Recessed Mini Light IP67

Superlight SL3054 is a very low profile LED fitting suitable for recess mounting in floors, decking and pavers. The fitting is fabricated from stainless steel and features high brightness 3350 SMD LED technology which delivers strong light output whilst minimising energy consumption.

### SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	0.7W
Facia Configuration:	58x58mm
Fitting Trim Dimensions:	51x51mm
Cutout Dimensions:	9mm
Overall Depth:	SMD3350
LED Classification:	8
LED Quantity:	Brushed Steel
Colour/Finish:	80lm/W
Typical Light Source Efficacy:	High Intensity Glass
Diffuser Material:	120°
Beam Angle:	Walk-Over Rated
Mechanical Rating:	-10 ~ +40°C
Recommended Ambient Temperature:	16.7million + (RGB Version)
Compatible Control Options:	DALI, DMX, 1-10V
IP Protection Rating:	IP67

### PHOTOMETRIC INFORMATION

- SL3053-15 CCT: 6000K CRI: →80 ●
- SL3053-17 CCT: 4000K CRI: →80 ●
- SL3053-21 CCT: 3000K CRI: →80 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Landscape lighting, driveways and pathway lighting, display cabinets, furniture lighting, marine & automotive applications, floor lighting, deck lighting.

### 3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CONTROL & DIMMING COMPATIBILITY

Superlight SL3054 is dimmable using any superlight constant voltage dimming controller.

Specific dimming options include PWM, DALI, DMX, 1-10V

RGB option is colour-controllable via Superlight RGB LED Controller

### ORDERING INFORMATION

- SL3054-21 Superlight Stainless Steel Recessed LED 58x58mm 3000K ●
- SL3054-17 Superlight Stainless Steel Recessed LED 58x58mm 4000K ●
- SL3054-15 Superlight Stainless Steel Recessed LED 58x58mm 6000K ●

