

## Superlight Grid-100 LED Downlight Series

The Superlight Grid series is a high quality range of LED downlight fittings. The product is suitable for architectural use in both residential and commercial projects. Grid-100 downlights feature a low profile and are constructed from premium materials. The Grid 100 series is available in one, two or three gang configurations.

### SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	45W
Trim Dimensions:	112x280mm
Fixture Depth	69mm
Ceiling Cutout:	97x267mm
LED Classification:	Sharp COB 350mA
LED Quantity:	3x15W
Fixture Material:	Extruded Body & Aluminium Reflector
Typical Light Source Efficacy:	90lm/W
Light Source CRI	90
Beam Angle Options:	25°/45°/55°
Frosted Lens Option:	Optional Frosted Lens - 70° Beam
Adjustable Tilt Angle:	360° Swivel + 35° Tilt
Recommended Ambient Temperature:	-10 ~ +40°C
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

- SL3393-15 CCT: 5000K CRI: →90 ●
- SL3393-17 CCT: 4000K CRI: →90 ●
- SL3393-21 CCT: 3000K CRI: →90 ●
- SL3393-27 CCT: 2700K CRI: →90 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Residential and commercial interior projects, retail spaces, shopping malls, show-rooms, hospitality projects, hotels, common areas, galleries and display areas, shoplighting, high ceiling lighting, airports, museums.

### CONTROL & DIMMING COMPATIBILITY

Superlight Grid-100 LED downlights are supplied with phase control dimmable LED drivers  
Optional DALI dimmable LED driver is available by special request  
Optional 1-10V dimmable LED driver is available by special request

### CUSTOMIZATION OPTIONS

Fixture trim can be refinished in Black/Silver/Satin Chrome  
Optional DALI dimmable LED driver available by special request

\*\*Custom options may be subject to minimum order quantities

### ORDERING INFORMATION

- SL3393D\*\*-15 Superlight Grid-100 Series LED Downlight 3x15W 5000K ●
- SL3393D\*\*-17 Superlight Grid-100 Series LED Downlight 3x15W 4000K ●
- SL3393D\*\*-21 Superlight Grid-100 Series LED Downlight 3x15W 3000K ●
- SL3393D\*\*-27 Superlight Grid-100 Series LED Downlight 3x15W 2700K ●

\*\*Specify Beam angle: 25°/45°/55°

\*\*Frosted lens version also available - 70° Beam Angle

