

## SATURN SERIES LED TRACK SPOTLIGHT

The Superlight Saturn fitting is a versatile track-mount or surface-mounted spotlight suitable for residential or commercial lighting applications. The high quality fitting can be configured to suit any standard lighting track including single circuit and three circuit options. Available accessories include a surface mounted base which converts the Saturn to a stand-alone light fitting, as well as honeycomb anti-glare baffle.

### SPECIFICATIONS

Input Voltage:	240V
Power Consumption:	20W/30W
Dimensions:	88(dia) x 280(h)mm
LED Classification:	CREE CDX
Colour/Finish:	WHITE/BLACK/SILVER
Typical Efficacy:	87lm/W
Beam Angle Options:	15° 24° 38° 60°
Track Adaptor:	Single-Circuit / Three-Circuit
Optional Accessories:	Surface Mount Base / Honeycomb Baffle
Adjustable Angle:	Horizontal 250° Vertical 90°
Fixture Material:	Alloy + Polycarbonate
Recommended Ambient Temperature:	-20°C~+50°C
IP Protection Rating:	IP20
LED Drive Current:	700mA

### PHOTOMETRIC INFORMATION

- Saturn Series CCT: 2700K CRI: →90 ●
- Saturn Series CCT: 3000K CRI: →90 ●
- Saturn Series CCT: 4000K CRI: →90 ●
- Saturn Series CCT: 5000K CRI: →90 ●

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Applications include task lighting spotlighting in offices, boardrooms, kitchen island lighting, museums, galleries, retail environments, cafes, etc

### 3D Modelling & Lighting Design

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

### CUSTOMIZATION OPTIONS

- Optional honeycomb glare baffle
- Optional surface mount base for stand-alone installation
- Fitting colour options Silver/Black/White
- Can be supplied with either 1-circuit or 3-circuit track adaptor
- DALI or 1-10V dimmable options available by request

### ORDERING INFORMATION

- SL4642 Superlight Saturn LED Fitting – Dimmable 20W Single-Circuit
- SL4643 Superlight Saturn LED Fitting – Dimmable 30W Single-Circuit
- SL4742 Superlight Saturn LED Fitting – Dimmable 20W Three-Circuit
- SL4743 Superlight Saturn LED Fitting – Dimmable 30W Three-Circuit

\*\* Specify fitting colour: BK/SV/WH \*\* Specify DALI or 1-10V dimming option

\*\* Specify beam angle: 15°/24°/38°/60°

