

SL9508 HIGH POWER LED SUPERFLOOD FITTING

The SuperFlood is a highest quality LED floodlight/wall-washer incorporating high power Luxeon LEDs for maximum illumination and performance. The fittings have a high-grade metal construction with tempered glass visor and are supplied complete with adjustable stainless steel bracket.

SPECIFICATIONS

Input Voltage:	24VDC
Standard Dimensions (L x W x H):	348 x 80 x 125mm
Max Power Consumption (Watts):	27W
LED Quantity:	9
LED Classification:	Max 3W Luxeon High Power
Operating Temperature:	-20°C ~ +80°C
Standard Beam/Viewing Angle:	25°
No of Possible Defined Colours:	16.7 Million + (RGB Version)
Potential Illumination Distance:	45-55mtrs
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

- SL9508-15 CCT: 6500K CRI: →85 ●
- SL9508-21 CCT: 3200K CRI: →82 ●
- SL9508-35 RGB Colour Controllable ●●●

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Ideally suited for high end washing applications such as nightclubs wall-washing, architectural lighting, hotels, plazas, corporate colour-schemes, special events, venues & productions etc.

3D MODELLING & LIGHTING DESIGN

Superlight can provide detailed 3D modelling and lighting design services for your project, including wiring schematics and lighting control system design. Contact us for more information.

CUSTOMIZATION OPTIONS

Superlight constant voltage LED controller
Superlight DMX512, DALI Controller

ORDERING INFORMATION

- SL9508-15 Superflood LED RGB Wall Washer 24VDC COOL WHITE ●
- SL9508-21 Superflood LED RGB Wall Washer 24VDC WARM WHITE ●
- SL9508-35 Superflood LED RGB Wall Washer 24VDC RGB ●●●

