

SUPERLIGHT DL61 COMMERCIAL LED DOWNLIGHT FIXTURE

Superlight DL61 Series is a high quality commercial downlight fixture that incorporates a high performance Zhaga LED module. The series is designed with high performance low-glare reflector and advanced LED optics. The fittings are available in a wide range of beam angle options and other configuration options.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	18W / 24W / 35W
Downlight Configuration:	Fixed Downlight
Trim Diameter:	205mm
Ceiling Cutout:	185mm
LED Classification:	Zhaga LED Module
Colour/Finish:	White Trim with Silver Reflector
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	>95 High CRI Version)
Beam Angle Options:	16° / 24° / 40°
Optional Accessories:	DALI Dimmable LED Driver
Recommended Ambient Temp:	-10°-40°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL61 Series	CCT: 6500K CRI: >95 (High CRI Version)
SL61 Series	CCT: 4200K CRI: >95 (High CRI Version)
SL61 Series	CCT: 6500K CRI: >95 (High CRI Version)

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include commercial spaces, galleries, museums, hospitality, offices, airports, retail shopping centres etc.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL6118	Superlight DL65 Series LED Downlight 18W
SL6124	Superlight DL65 Series LED Downlight 24W
SL6135	Superlight DL65 Series LED Downlight 35W

** Specify CCT 3200K / 4200K / 6500K

** Specify Beam angle: 16° / 24° / 40°

CUSTOMISATION OPTIONS

Specific CCT colour temperature by special request

Customisable beam angles available by special request

DALI dimmable LED driver available by special request

* Minimum order quantities apply for custom options

