

SL2251 SURFACE MOUNT LED DOWNLIGHT

Superlight SL2251 is a surface mounted LED downlight suitable for general purpose downlighting applications. The fittings incorporate a powerful 6W SMD LED module and integral LED driver.

SPECIFICATIONS

Input Voltage:
Max Power Consumption:
LED Drive Current:
LED Classification:
Beam Angle:
Standard Finish:
LED Driver:
Dimensions Height:
Dimensions Diameter:
IP Rating:
Recommended Operating Temp:

PHOTOMETRIC INFORMATION

SL2251-15	CCT: 6500K CRI: >80
SL2251-17	CCT: 4200K CRI: >85
SL2251-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General area lighting in commercial and residential applications, Concrete slab ceilings.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL2252-15	6W Surface Mount LED Downlight 6500K COOL WHITE
SL2252-17	6W Surface Mount LED Downlight 4200K NEUTRAL WHITE
SL2252-21	6W Surface Mount LED Downlight 3200K WARM WHITE

CUSTOMISATION OPTIONS

Fitting colour can be refinished
Remote mounted dimmable driver available by request
Customisation options are subject to availability and minimum order quantities

