

SL2265 4W LED JOINERY CABINET DOWNLIGHT

The SL2264/SL2265 is a low profile LED downlight ideally suited to joinery lighting, display cabinets, showcases & retail stores. The fittings are also ideal for small-space downlighting where a low-profile fitting is required. They are supplied with optional surface mount spacer ring which allows them to be surface mounted if required.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	4W
LED Quantity:	36
LED Classification:	Micro SMD
Standard Beam Angle:	120°
LED Drive Current:	350mA
IP Rating:	IP40
Trim Dimensions:	70mm
Recessed Cutout:	65mm
Mounting Depth:	13.5mm
Recommended Ambient Temp:	-20 ~ +65°C
Trim Finish:	Matt White or Matt Silver
Dimmable:	Use Compatible LED Dimmer
Lens:	Frosted PC Lens

PHOTOMETRIC INFORMATION

SL2265-21 Warm White	CCT 3200K CRI >85
SL2265-15 Cool White	CCT 6500K CRI >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Joinery & display cabinets, Kitchen & bathroom joinery units, Showcases & retail displays, Small space general downlighting.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL2265-21	WHITE LED Cabinet Light 12VDC 3200K Warm White
SL2265-15	WHITE LED Cabinet Light 12VDC 6500K Cool White
SL2264-21	SILVER LED Cabinet Light 12VDC 3200K Warm White
SL2264-15	SILVER LED Cabinet Light 12VDC 6500K Cool White

CUSTOMISATION OPTIONS

Trim colour can be refinished
Fitting can be recessed or surface mounted
Surface mount spacer ring is included
Customisation options are subject to availability and minimum order quantities.

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

