

SL2269 70MM MINIATURE LED DOWNLIGHT

Superlight SL2269 LED Downlight is a compact fixture with excellent characteristics and performance. It has extremely compact dimensions making it ideal for installations that have extremely low ceiling cavity depth.

SPECIFICATIONS

Driver Input Voltage:	240V
Max Power Consumption:	13W
LED Quantity:	1
LED Classification:	High Power Sharp LED
Standard Beam Angle:	60°
LED Drive Current:	450mA
IP Rating:	IP44
Physical Dimensions:	Trim: 85mm
Ceiling Cutout:	70mm
Minimum Ceiling Depth Required:	55mm
Dimmable:	Use Compatible LED Controller
Recommended Ambient Temp:	-20 ~ +55°C



PHOTOMETRIC INFORMATION

SL2269-21 Warm White	CCT 3000K CRI >90
SL2269-17 Neutral White	CCT 4200K CRI >85
SL2269-15 Cool White	CCT 6000K CRI >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General downlighting applications with demanding space limitations.
Residential and commercial projects.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL2269-15	70mm LED Downlight 13W Cool White 6000K
SL2269-21	70mm LED Downlight 13W Warm White 3000K
SL2269-17	70mm LED Downlight 13W Neutral White 4200K

CUSTOMISATION OPTIONS

Fixture trim colour can be refinished
Glass lens can be frosted by request
Minimum order quantity applies for custom options

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.