

SL2278 MINI LED DOWNLIGHT ROUND

Superlight Mini LED downlights are suitable for applications where a small fitting is required, such as joinery & furniture lighting, marine applications, discrete architectural lighting, kitchen & bathroom lighting etc.

The mini LED downlight has excellent light output thanks to the powerful CREE 3W LED. The fittings can be either recessed or surface-mounted using the optional surface-mount base.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption(Watts):	3W
LED Classification:	High Power Cree 3W
Colour Temperature (cw/ww):	6500K/3200K
Beam Angles Available:	30° or 60°
Mounting Options:	Recessed or Surface Mount
Trim Dimensions:	33 mm
Fixture Depth:	22mm
Operating Temperature:	-5 ~ +55°C
Dimmable:	Yes with Superlight LED Dimmer

PHOTOMETRIC INFORMATION

SL2278-15 CCT: 6500K CRI: >85

SL2278-21 CCT: 3200K CRI: >90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Joinery & Furniture Lighting, Marine Applications, Discrete architectural lighting, Kitchen & bathroom lighting etc.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL2278-15	Round 3W Mini LED Downlight 30° 6500K COOL WHITE
SL2278-21	Round 3W Mini LED Downlight 30° 3200K WARM WHITE
SL2279-15	Round 3W Mini LED Downlight 60° 6500K COOL WHITE
SL2279-21	Round 3W Mini LED Downlight 60° 3200K WARM WHITE

CUSTOMISATION OPTIONS

Trim colour can be refinished

30° or 60° lens options

Customisation options are subject to availability and minimum order quantities.



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.